

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61N 1/375, H01R 4/48 // 4/26		A1	(11) International Publication Number: WO 00/32268 (43) International Publication Date: 8 June 2000 (08.06.00)
<p>(21) International Application Number: PCT/SE99/02083</p> <p>(22) International Filing Date: 15 November 1999 (15.11.99)</p> <p>(30) Priority Data: 9804138-7 30 November 1998 (30.11.98) SE</p> <p>(71) Applicant (<i>for all designated States except US</i>): PACESETTER AB [SE/SE]; S-175 84 Järfälla (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (<i>for US only</i>): HILL, Rolf [SE/SE]; Gösvägen 8, S-175 55 Järfälla (SE).</p> <p>(74) Common Representative: PACESETTER AB; Patent Department, S-175 84 Järfälla (SE).</p>		<p>(81) Designated States: US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
<p>(54) Title: DEVICE IN CONNECTION WITH PACERS</p>			
<p>(57) Abstract</p> <p>The invention relates to a locking device (1) for a female connector part for cooperation with an elongate, male connector part (30), said female connector part being intended for use in a pacer housing. Said female connector part comprises a longitudinal bore defining a longitudinal space for said locking device. Said locking device comprises one or several tongues (19, 19') being swingable between two positions, a first position in which the tips of the tongues (19, 19') can engage said male elongate connector part (30) and a second position in which the tips of the tongues (19, 19') will not engage the male elongate connector part (30). Said tongues are biased towards said first position by means of a spring force. A pivot (9) is associated with each tongue and each tongue has a first part engaging said connector means (30) and being located on one side of said pivot and a second part being located on the other side of said pivot. Longitudinally acting means (4) are provided to act on said second part of said tongues (19, 19') for actuating said tongues from said first position against said bias to said second position.</p>			